

An electrically insulating dielectric boot with an integral steel toe cap and vulcanized rubber sole for superior slip resistance. The Respirex Dielectric boot provides protection of up to 20kV over the complete boot for over 8 hours, and 35kV over the sole for 3 minutes.



20kV
Protection
For Over Eight
Hours

Boot Shaft

- Yellow dielectric compound shaft
- 200 Joule Epoxy coated Steel toe cap to EN ISO 20345
- Seamless construction
- Kick off lug
- Extra shin protection
- Adjustable height
- Ankle guard
- Non-wicking knitted nylon lining
- Comfort insole (removable and machine washable)
- REACH Compliant

Boot Sole

- Blue vulcanized rubber sole for maximum grip - 30% better than a conventional safety boot sole
- Slip resistance performance twice that required by EN 13287 SRA and SATRA TM144 standards
- Cleated outsole for maximum grip
- Two to three times the wear resistance of conventional soles
- Fuel and oil resistant
- Greater cut resistance than conventional soles
- Resistance to hot contact 60 seconds 300°C.
- Energy absorbing tunnel system conforms to EN 20345 E
- Cold insulation to EN ISO 20345

Care

- Machine washable at up to 40°C
- Shelf life of over 10 years

Electrical Protection

Complete boot: 20 kV.....8 hours no damage
5 kV.....<5mA Leakage current

Sole: 35 kV.....3 minutes no damage

Certification

Safety Footwear EN ISO 20345:2011
- SB E CI HRO SRA FO

Electrically Insulating Footwear EN 50321:1999 Class 0
prEN 50321:2013 Class 2

Dielectric Footwear ASTM F1117

Personal Protective Equipment PPE DIR 89/686/EEC

Sizes

UK	3	4	5	6	7	8	9	10	11	12	13	14	15
EU	35	36	37	39	41	42	43	44	45	46	47	49	50
US	4	5	6	7	8	9	10	11	12	13	14	15	16



Vulcanized Rubber Sole



Butts of Bawtry

Station Yard Bawtry Doncaster South Yorks DN10 6QD UK

Tel: 0044 (0)1302 710868 Fax: 0044 (0)1302 719481

Web: www.buttsofbawtry.com Email: info@buttsofbawtry.com