



POWER & RELIABILITY

THE 6 MOST POWERFUL BOOSTERS OF THE WORLD CERTIFIED BY NATO (NSN)

The Nato Armies can count on the power and reliability of the **Ceteor** jump starters to start JEEP's, heavy trucks, battle tanks, and other engines 12V or 24V.

Indispensable models for Nato Armies:



Jump starter SOS or PPS 12V-1200CA

PETROL OR DIESEL

The ideal tool to jump start 12V diesel vehicle without battery up to 250HP.
Ex.: jeep, 4x4, commercial vehicles...



Jump starter SOS or PPS 12/24V-2400/1200CA

PETROL OR DIESEL

Perfect to start engines up to 1500 HP which have been stationary for a long time, in extreme temperature conditions from -30° to +60°C, without batteries. (trucks, tanks, busses, turbine jets...)
Ex.: able to start a 1500 HP 38l Leopard tank without batteries.

Also available in 24V (see technical specifications)*



Butts of Bawtry

Station Yard Bawtry Doncaster South Yorks DN10 6QD UK

Tel: 0044 (0)1302 710868 Fax: 0044 (0)1302 719481

Web: www.buttsofbawtry.com Email: info@buttsofbawtry.com

Jump starter**SOS or PPS 12/24V-3200/1600CA***For twice as much power:***SOS or PPS 12/24V-6400/3200CA****PETROL OR DIESEL**

Perfect for extreme use, these models on wheels makes handling easier in the workshop. They can start diesel engines up to 1500 HP which have been stationary for a long time, in extreme temperature conditions from -30° to +60°C, without batteries.

Also available in 24V (* see technical specifications)

**RECOMMENDED OPTIONS****EASY AND SAFE CONNECTIONS**

To ensure efficient and professional jump starting, **Ceteor** offers several auxiliary cables and connections suitable for the military sector.

Reference	Description	
For SOS Portable		
860016	3m 50mm ² - Cable with clamps 850A & red connector	
860015	2m 50mm ² - Cable with NATO plug & red connector	
860032	1,2m 2x35mm ² - Cable with double NATO plug & red connector	
976001	2m 50mm ² - Cable with 'Park Plug' (aviation) & red connector	
For SOS Mobile		
860034	4m 70mm ² - Cable with clamps 850A & grey connector	
860024	2m 50mm ² - Cable with NATO plug & grey connector	
860025	4m 50mm ² - Cable with NATO plug & grey connector	
860033	3m 2x50mm ² - Cable with double NATO plug & grey connector	
976002	2m 70mm ² - Cable with 'Park Plug' (aviation) & grey connector	

**TECHNICAL SPECIFICATIONS**

Voltage
Cranking amps (CA)
Peak amps (PA)
NSN (Nato Stock Number)

Reference
Cable length
Radaflex® welding cable size
Type of clamps
12V Output
Reverse polarity system
Auxiliary connector
Net weight

12V 1200CA		12/24V 2400/1200CA		12/24V 3200/1600CA		12/24V 6400/3200CA	
12V		12/24V		12/24V		12/24V	
1200 A		2400/1200 A		3200/1600 A		6400/3200 A	
3100 A		6200/3100 A		7750/3875 A		15550/7750 A	
✗		2990-13-119-1843		2990-13-119-1844		2990-13-121-2847	
SOS	PPS	SOS	PPS	SOS	PPS	SOS	PPS
860003k	520003k	760008k	520008k	960000k	560000k	960001k	560002k
1,50 m	1,55 m	1,35 m	1,35 m	1,95 m	2,10 m	1,95 m	2,10 m
35 mm ²	50 mm ²	50 mm ²	50 mm ²	70 mm ²	70 mm ²	70 mm ²	70 mm ²
850 A	850 A	850 A	850 A	850 A	850 A	850 A	850 A
16 A	16 A	16 A	✗	16 A	✗	16 A	✗
☉	☉	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓	✓
14,5 kg	14,3 kg	24,8 kg	24,8 kg	55 kg	69 kg	68,5 kg	82,5 kg
✗	✗	760005k	520005k	960002k	560002k	960003k	560003k
✗		2990-13-119-2139		2990-13-119-2140		2990-13-119-2141	

Legend: ✓ yes ✗ no ☉ option