

## PRODUCT INFORMATION

# BITEX CLEAR

## Clear Road Marking Primer

### Description

An effective solvent-based primer for bonding thermoplastic materials to concrete and worn bituminous surfaces. Its low viscosity facilitates deep penetration into substrates. Bitex Clear can be applied by spraying or by brush or roller.

### Uses

To improve the adhesion of thermoplastic materials to concrete, worn asphalt or other bituminous surfaces.

### Benefits

- Virtually colourless
- Superior adhesion enhancement
- Ready to use - no mixing required
- Fast drying
- Easy to apply

Technical	
Coverage Approx.	12 to 15 m <sup>2</sup> per litre @ 66 to 83 microns wet film thickness
Specific Gravity (SG)	Approx. 0.86
Flash Point	-5°C
Application Surface Temp	1 to 50°C
Drying Time	Touch dry in 10 to 15 minutes but over-coating should not take place within 30 minutes

### Colours

Clear

### Surface Preparation

Surface must be clean, dry and free from any contamination including dust, dirt oil, grease, laitance and curing agents. Particular attention should be given to ensuring the surface is free from salt, ice and moisture.

### Product Application

Application is by spray, brush or roller. The prepared surface must be totally covered with a thin, even coating of Bitex Clear. Never pour onto the surface. Ensure Bitex Clear is thoroughly dry before applying subsequent thermoplastic materials. It is always

advisable to try a test area first before proceeding with the main application.

### Aftercare

Not normally necessary

### Packaging and Storage

Bitex Clear is supplied in 5 litre steel drums. Store in a cool, dry, well-ventilated place. Shelf life is 3 years under normal conditions.

### Health and Safety

Bitex Clear contains flammable solvents. Keep away from sources of ignition. No smoking. See separate Safety Data Sheet

Published January 2009