

Caricabatterie Manuali / Manual Battery Chargers

Watt 140 - 220

Battery charger for all kinds of lead storage batteries with free electrolyte of 12 or 24 V.
Charging current regulation. Single phase 230 Volt power supply. Overload, short-circuits and polarity inversion safeguards.
Equipped with ammeter.
Characteristic "W" charge curve at decreasing current, according to DIN 41774 standard, (diagram represented in DIN 41772).
Manufactured in painted plate and plastic material in self-extinguishable polycarbonate.
Two years guarantee on all products.



Made in Italy



- Amperometro per l'indicazione della corrente erogata / *Ammeter for current indication;*
- Regolazione della corrente su tutti i modelli / *Current regulation in all models;*
- Collegamenti alla batteria con faston o pinze (in dotazione) / *Battery connections with terminals or clamps (equipped);*
- Fusibili di ricambio (in dotazione) / *Spare fuses (equipped);*
- Protezione termica a ripristino automatico contro i sovraccarichi *Thermic protection with automatic resetting against overloads;*
- Protezione a doppio fusibile contro inversioni di polarità e cortocircuiti / *Double fuse protection against polarity inversions and shortcircuits.*

Model	Mains Voltage 50/60 Hz 1 Ph Volt	Power Watt	Output Voltage Volt	Charge Current Eff. Amp	Charge Current Arith. Amp (d.c.)	Charge Current Regulation N°	Nominal Capacity to refer to Ah min max	Size mm	Weight kg	Cod. N
Watt 140	230	140	12/24	12/6	8	4	15 - 100	250 x 150 x 210	3,8	03030
Watt 220	230	220	12/24	18/10	12/7	4	15 - 180	250 x 150 x 210	5	03050